

D200

STABLE MiniPOS



Food & Beverage



Fashion & Retail



Transportation



CLASSIC



Powered by
Prolin



PCI 4
SRED

















2.4"
Display



Advanced
Connectivity

SPECIFICATIONS

	Operating System	Prolin
	Processor	32-bit ARM 11
	Memory	128M Flash + 64MB SDRAM
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Display	2.4" TFT Colour Display 320 x 240 Pixels Touch Screen (optional)
	Comms Configurations	Wi-Fi® 2.4GHz (optional) 3G (WCDMA) (optional) 2G (GPRS) (optional) Bluetooth®
	Battery	1900mAh 3.7V
	SIM / SAM	1 Micro SIM + 1 SAM
	Keys / Buttons	1 Numeric 5 Function Keys Touch-button Input
	Audio	1 Buzzer
	Ports	1 micro-USB2.0 1 RS232
	Physical	121 x 72 x 23mm, 165g (including battery)
	Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 93% Relative Humidity, Non-Condensing
	Certifications	PCI PTS 4.x SRED EMV Contact L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless American Expresspay Discover D-PAS JCB J/Speedy Mastercard TQM Visa Ready Mastercard MPOS

