SUNMI P3 MIX —





MIX, the all-in-one enterprise tablet.



Compatible with

SUNNI DMP



MIX your POS terminal to capture businesses anywhere, anytime.

10"high-resolution display and a built-in high speed printer make a mobile and desktop terminal.

MIX, design not only for payment.

Ergonomically designed for a comfortable grip. Professional scanner integrated 1D/2D barcode scanning. Aluminum-magnesium alloy frame and incell touchscreen make it strong yet slim and light.

MIX for higher performance.

Qualcomm hexa-core processor and 4GB RAM+32GB ROM for an assured strong performance.

MIX for wider extensibility.



Specially designed rotatable functional cradle enable cash drawer, handheld scanner and network among other accessories that boost your business.

*Both rotatable cradle and non-rotatable cradle options are available.





Accept any payment methods to ensure secure and stable payment processing.







QR Code Payment




Mobile Payment



All Pictures shown are for illustration purpose only, actual product may vary.

SUNMI P3 MIX Application Scenario







SUNMI P3 MIX Tech Specs

General Configuration

Product Model

T672

os

SUNMI OS (*based on Android 13)

Processor

Qualcomm hexa-core 2.4/1.9GHz

Memory

4GB RAM + 32GB ROM

Display

10.1" HD 1280*800 IPS

Camera

Front: 2MP FF QR Payment: 0.3MP FF

IC Card

Smart IC card/logic encryption contact card; ISO 7816/EMV/compliant; 5V/3V/1.8V

Magstripe Reader

1/2/3 track; Bi-directional card reading; ISO 7810/7811 compliant

NFC Reader

Type A&B card, MIFARE card, ISO/IEC 14443 and ISO 15693 compliant

Scanner

D professional scanner

Network

2G&3G&4G

Wi-Fi

2.4GHz/5GHz IEEE 802.11 a/b/g/n/ac

Bluetooth

3T2.1/3.0/4.2 support BLE

GPS

GPS, AGPS

Card Slot

2*Nano SIM+2*SAM 1*MicroSD

Speaker

1.2W

Battery

Removable Lithium battery 7.2V/2600mAh

Power Adapter

Input: AC 100 ~ 240V Output: DC 5V / 2A

Ports

1* Type-C 1* Type-A 1* Page pip on the

Button

1*Power on/off button 1*Volume (+/-) button 1*Scan button

Dimensions(L*W*H)

246*231*73mm

Total Weight

670g 58mm/710g 80mm

Cradle (optional)

3*USB Type A, RJ11, RJ45 Support USB OTG Support Ethernet

Cradle Customer Display (optional)

USB 6.7" touchscreen

Fingerprint

Only for logir

Environment

Printer

Operating temperature: $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Storage temperature: $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$

58 Version

Built-in 58mm thermal printer Print speed: 70mm/s Paper roll: Ф40mm Printer life: 100km

80 Version

Built-in 80mm thermal printer Print speed: 70mm/s Paper roll: Ф40mm Printer life: 100km